



Unique identification code of the product type: **CELOTEX XPS 300 SL FS**  
 Intended use(s): **Thermal insulation for buildings**  
 Manufacturer: **SOPREMA nv**  
**Bouwelven 5 – 2280 Grobbendonk**  
**Belgium**  
 System(s) of AVCP: **System 3**  
 Harmonised standard: **EN 13164:2012+A1:2015**  
 Notified body/ies: **0751-1136-1173**

## Declared performances

Essential characteristics <sup>5</sup>	Performances	Test standard	Harmonised technical specification
Thermal conductivity - $\lambda_D$ (W/(m.K))	40 ≤ d ≤ 245 mm 245 < d ≤ 280 mm	0,032 <sup>1</sup> 0,033 <sup>1</sup>	EN 12667
Thermal resistance - $R_D$ (m <sup>2</sup> .K/W)	40 - 245 mm 250 - 280 mm	1,25 - 7,65 <sup>1</sup> 7,55 - 8,45 <sup>1</sup>	EN 12667
Thickness tolerance - $d_N$		T1	EN 823
Reaction to fire		F	EN 13501-1
Durability of reaction to fire against heat, weathering, ageing/degradation		F <sup>2</sup>	EN 13501-1
Durability against heat, weathering, ageing/degradation			
- Thermal conductivity - $\lambda_D$ (W/(m.K))	40 ≤ d ≤ 245 mm 245 < d ≤ 280 mm	0,032 0,033	EN 12667
- Thermal resistance - $R_D$ (m <sup>2</sup> .K/W)	40 - 245 mm 250 - 280 mm	1,25 - 7,65 7,55 - 8,45	EN 12667
- Dimensional stability (≤ 5 %)		DS(70,90)	EN 1604
- Freeze-thaw resistance (%)	40 ≤ d < 80 mm 80 ≤ d ≤ 280 mm	FTCD1 FTCD2 <sup>3</sup>	EN 12091
Compressive strength at 10 % deformation (kPa)		CS(10\Y)300	EN 826
Tensile strength perpendicular to faces (kPa)	40 ≤ d < 80 mm 80 ≤ d ≤ 280 mm	NPD TR200	EN 1607
Durability of compressive creep against ageing/degradation (kPa)	40 ≤ d < 60 mm 60 ≤ d ≤ 280 mm	NPD CC(2/1,5/50)130	EN 1606
Long term water absorption by total immersion (% v)		WL(T)0,7	EN 12087
Long term water absorption by diffusion (% v)	40 ≤ d < 60 mm 60 ≤ d < 100 mm 100 ≤ d ≤ 280 mm	WD(V)3 WD(V)2 WD(V)1	EN 12088
Water vapour diffusion resistance - $\mu$		150	EN 12086
Release of dangerous substances to the indoor environment		NPD <sup>4</sup>	-
Continuous glowing combustion		NPD <sup>4</sup>	-

EN 13164:2012 + A1:2015

NPD = no performance determined

1) The variation due to aging of the thermal conductivity and resistance has been taken into account in the indicated performance

2) The fire performance does not deteriorate with time

3) Multi-layer thermobond boards

4) In the absence of European harmonized test methods, verification and declaration on release and content has to be done taking into account national provisions in the place of use

5) Also applicable and valid for multiple layers

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: **Marnix Derks, Technical Director**  
**Grobbendonk, 23/09/2024**

**SOPREMA NV** reserves the right to amend the composition of its material and consequently their prices, without prior notice. For this reason, all orders will be accepted only in accordance with the conditions and technical specifications in force at the date of order.